

Service Connectors Blocks

- Black Urea Phenolic

**GREEN
BROOK**

NORSLO

- + Black urea phenolic
- + Easy knockout entries
- + Lids can be sealed for security
- + CB1/CB2/CB3 & CB6 conform to BS EN 60998-1 & BS EN 60998-2-1
- + CB9 conforms to BS EN 60999-1 & BS EN 60999-2



	CB1	CB3	CB2	CB6	CB9
Description	100A, 25mm ²	100A, 35mm ²	100A, 25mm ²	100A, 35mm ²	200A, 70mm ²
No of Ways	5 Way	5 Way	2 x 5 Way	2 x 5 Way	6 Way
Pack Qty	20	20	10	10	1
Barcode	5012739 616808	5012739 616822	5012739 616815	5012739 616846	5012739 616853
Colour	Black Urea Phenolic				
Power Rating	230V AC ~ 50Hz				
No of Poles	Single	Single	Double	Double	Single
Torque Setting	2.5Nm Screw size M6	3.5Nm Screw size M8	2.5Nm Screw size M6	3.5Nm Screw size M8	3.5Nm Screw size M8
Operating Temp	-10°C - +40°C				
Product Weight	132g	188g	290g	493g	585g
Dimensions H x W x D	H64 x W47 x D38mm	H64 x W47 x D38mm	H89 x W65 x D55mm	H104 x W66 x D67mm	H125 x W64 x D55mm
Guarantee	1 Year				
Conforms To	BS EN 60998-1 & BS EN 60998-2-1				BS EN 60999-1 & BS EN6099-2